

VS100 Series GPS Compass Professional Heading and Positioning Receiver



VS100™

Powered by
Crescent

Precise applications demand the heading and positioning performance of the VS100™ Series GPS Compass. Ideal for professional machine control and navigation applications, the VS100 delivers reliable accuracy at significantly less cost than competitors products or traditional methods.

The VS100 Series Receiver, with its display and user interface, can be conveniently installed near the operator. The two antennas are mounted separately and with a distance between them to meet the desired accuracy.

Key VS100 Series Advantages

- Affordable solution delivers 2D GPS heading accuracy better than 0.1 degree rms
- Differential positioning accuracy of less than 60 cm, 95% of the time
- Integrated gyro and tilt sensor deliver fast start-up times and provide heading updates during temporary loss of GPS
- Fast heading and positioning output rates up to 20 Hz
- Differential options including SBAS (WAAS, EGNOS, etc.) and optional beacon differential
- COAST™ technology maintains accurate solutions for 40 minutes or more after loss of differential signal
- The status lights and menu system make the VS100 series easy to monitor and configure

VS100 Series GPS Compass

GPS Sensor Specifications

Receiver Type:	L1, C/A code, with carrier phase smoothing
Channels:	Two 12-channel, parallel tracking (Two 10-channel when tracking SBAS)
Update Rate:	Standard 10 Hz, optional 20 Hz (position and heading)
Horizontal Accuracy:	< 0.6 m 95% confidence (DGPS)* < 2.5 m 95% confidence (autonomous, no SA)**
Heading Accuracy:	< 0.30° rms @ 0.5 m antenna separation < 0.15° rms @ 1.0 m antenna separation < 0.10° rms @ 2.0 m antenna separation
Pitch / Roll Accuracy:	< 1° rms @ 0.5 m antenna separation
Rate of Turn:	90°/s max
Cold Start:	60s (No almanac or RTC)
Heading Fix:	< 20s
Satellite Reacquisition:	< 1s
Antenna Input Impedance:	50Ω

Beacon Sensor Specifications (VS110 version)

Channels:	2-channel, parallel tracking
Frequency Range:	283.5 to 325 kHz
Operating Modes:	Automatic (signal strength), Database and Manual
Compliance:	IEC 61108-4 beacon standard

Communications

Serial ports:	2 full duplex
Interface Level:	RS-232C
Baud Rates:	4800 - 57600
Correction I/O Protocol:	RTCM SC-104, L-Dif (Hemisphere GPS proprietary)
Data I/O Protocol:	NMEA 0183, Crescent binary, L-Dif (Hemisphere GPS proprietary)
Timing Output:	1 PPS (HCMOS, active high, rising edge sync, 10 kΩ, 10 pF load)
1 PPS Accuracy:	50 ns

Power

Input Voltage:	9 to 36 VDC
Power Consumption:	< 5 W
Current Consumption:	< 360 mA @ 12 VDC
Antenna Voltage Output:	5 VDC
Antenna Short Circuit Protection:	Yes

Copyright © 2009 Hemisphere GPS. All rights reserved. Specifications subject to change without notice. Hemisphere GPS and the Hemisphere GPS logo and Crescent and the Crescent logo are trademarks of Hemisphere GPS.

Environmental

Operating Temperature:	-32°C to +74°C (-25°F to +165°F)
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Shock and Vibration:	EP 455
EMC:	FCC Part 15, Subpart B, Class B, CISPR22, CE

Mechanical

Dimensions:	189 mm L x 114 mm W x 71 mm H (7.4" L x 4.5" W x 2.8" H)
Weight:	0.86 kg (1.9 lb)
Status Indication:	Power, primary GPS lock, secondary GPS lock, differential lock, and heading lock
Power Switch:	Miniature push-button
Power Connector:	2-pin, micro-Conxall
Data Connectors:	DB9-female x2
Antenna Connectors:	TNC-female x2

Aiding Devices

Gyro:	Single axis gyro provides reliable <1° heading for periods up to 3 minutes when loss of GPS lock has occurred
Tilt Sensor:	Assists in fast start up of RTK solution

* Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for local services), and ionospheric activity
** Depends on multipath environment, number of satellites in view, and satellite geometry

VS100 Series Heading Performance vs. Antenna Separation

